



BETONÁRSKE OCELE

PLECHY

TYČE PROFILOVÉHO PRIEREZU

RÚRY

UZAVRETÉ PROFILY

ZVÁRANÉ SIETE

DRÔTY


ŠPECIÁLNE PROFILY

VÝROBKY

BETONÁRSKE OCELE

hrebienkové v tyčičach

DIN 488-2	DIN 488-1	PN-H-93220:2006
B500A	BS1500M, BS1500KR	
B500B	BS1500S	
B500C		B500SP




Hrúbka	Dĺžka		Teoretická hmotnosť
d (mm)	(mm)		(kg/m)
6,00	6 000	12 000	0,222
8,00	6 000	12 000	0,395
10,00	6 000	12 000	0,617
12,00	6 000	12 000	0,888
14,00	6 000	12 000	1,210
16,00	6 000	12 000	1,580
18,00	6 000	12 000	2,000
20,00	6 000	12 000	2,470
22,00	6 000	12 000	2,980
25,00	6 000	12 000	3,850
28,00	6 000	12 000	4,830
32,00	6 000	12 000	6,310

BETONÁRSKE OCELE

hrebienkové vo zvitkoch


DIN 488-2	DIN 488-1	PN-H-93220:2006
B500A	BSt500M, KR	
B500B	BSt500WR	
B500C		B500SP



Menovitý rozmer	Dĺžka	Teoretická hmotnosť
d (mm)	(mm)	(kg/m)
4,00	zvitok	0,099
5,00	zvitok	0,154
6,00	zvitok	0,222
8,00	zvitok	0,395
10,00	zvitok	0,617
12,00	zvitok	0,888
14,00	zvitok	1,210
16,00	zvitok	1,580

VALCOVANÝ DRÔT

valcovaný za tepla



EN 10025-2	ASTM A510M
S235JR + AR	SAE 1008

Menovitý rozmer*	Dĺžka	Teoretická hmotnosť
d (mm)	(mm)	(kg/m)
5,50	zvitok	0,186
6,00	zvitok	0,222
6,50	zvitok	0,261
7,00	zvitok	0,302
7,50	zvitok	0,347
8,00	zvitok	0,395
8,50	zvitok	0,446
9,00	zvitok	0,499
9,50	zvitok	0,556
10,00	zvitok	0,617
11,00	zvitok	0,746
12,00	zvitok	0,888

* iné rozmery a akosti po dohode