

PLECHY

BETONÁRSKE OCELE

TYČE PROFILOVÉHO PRIEREZU

RÚRY

UZAVRETÉ PROFILY

ZVÁRANÉ SIETE

DRÔTY

ŠPECIÁLNE PROFILY


VÝROBKY

ZVÁRANÉ SIETE

z rebrovaného drôtu

DIN 488

B500A



Označenie	≥ drôtu	Šírka × dĺžka	Rozmer oka	Teoretická hmotnosť
		(mm)		
KA 16	4/4	2 000 × 3 000	100/100	11,880
KA 17	4/4	2 000 × 3 000	150/150	8,120
KA 18	4/4	2 000 × 3 000	200/200	5,940
Q 84	4/4	2 150 × 5 000	150/150	14,450
AQ 42	4,2/4,2	2 400 × 6 000	100/100	31,390
KD 35	5/5	2 000 × 3 000	100/100	18,500
KD 37	5/5	2 000 × 3 000	150/150	12,640
KD 36	5/5	2 000 × 3 000	200/200	9,250
Q 131	5/5	2 150 × 5 000	150/150	22,500
AQ 50	5/5	2 400 × 6 000	100/100	44,380
KH 20	6/6	2 000 × 3 000	150/150	18,200
KH 30	6/6	2 000 × 3 000	100/100	26,640
KH 31	6/6	2 000 × 3 000	200/200	13,320
Q 188A	6/6	2 300 × 6 000	150/150	41,700
AQ 60	6/6	2 400 × 6 000	100/100	63,940
AQ 70	7/7	2 400 × 6 000	100/100	86,980
KY 18/49	8/8	2 000 × 3 000	100/100	47,400
KY 50	8/8	2 000 × 3 000	150/150	32,400
KY 51/57	8/8	2 000 × 3 000	200/200	23,700
KY 81	8/8	2 150 × 5 000	100/100	85,910
Q 335 A	8/8	2 150 × 5 000	150/150	57,700
KY 85/95, AQ 80	8/8	2 400 × 6 000	100/100	113,800
KY 14/86	8/8	2 400 × 6 000	150/150	75,840

Poznámka: Možnosť dodania sietí aj na základe výkresovej dokumentácie.